## Parker Polyflex™ 2022N Series





Core tube: Polyamide

Pressure reinforcement: Two braided layers

of high tensile aramid fibre

Cover: Sea water resistant TPU

Standard Colour: Black

Temperature: -40°C up to +55°C















## 10,000 psi hose assemblies

## Features & Benefits

- lightweight by design
- small bend radius
- long continuous lengths available
- excellent abrasion resistance
- outstanding chemical resistance
- long service life due to high UV resistance
- can be perforated for gas use

#	0			0	(	2		<b>*</b>	$\mathbb{A}$		
	DN	size	mm	inch	mm	MPa	psi	MPa	psi	mm	kg/m
2022N-04V15-10K	6	-04	6.4	1/4	13.8	69	10,000	276	40,000	100	0.14
2022N-06V15-10K	10	-06	9.7	3/8	19.0	69	10,000	276	40,000	100	0.24
2022N-08V15-10K	12	-08	12.9	1/2	23.0	69	10,000	276	40,000	100	0.34

## Part Numbering - Standard Assemblies

700 bar hose	1 metre	3 metres	6 metres	10 metres
JIC 6 female swivel end connections	2380N/04-0606C-1M	2380N/04-0606C-3M	2380N/04-0606C-6M	2380N/04-0606C-10M
JIC 4 female swivel end connections	2380N-04-0406C-1M	2380N-04-0406C-3M	2380N-04-0406C-6M	2380N-04-0406C-10M
1/4" NPT male end connections	2380N/04-0401C-1M	2380N/04-0401C-3M	2380N/04-0401C-6M	2380N/04-0401C-10M
3/8" NPT male end connections	2380N/04-0601C-1M	2380N/04-0601C-3M	2380N/04-0601C-6M	2380N/04-0601C-10M
1/4" BSPP female swivel end connections	2380N/04-0492C-1M	2380N/04-0492C-3M	2380N/04-0492C-6M	2380N/04-0492C-10M



