

## Parker Polyflex™ 2440D-03V32 series



## Construction

Core tube: Polyoxymethylene

Pressure reinforcement: Four spiral layers of maximum tensile steel wire

Cover: Polyamide

Standard Colour: Blue







Temperature: -10°C up to +70°C



## 1800 bar hose assemblies

## Features &amp; Benefits

- lightweight by design
- small bend radius
- long continuous lengths available
- excellent abrasion resistance
- outstanding chemical resistance
- long service life due to high UV resistance
- can be perforated for gas use

#											
	DN	size	mm	inch	mm	MPa	psi	MPa	psi	mm	kg/m
2440D-03V32	5	-03	4.8	3/16	11.5	180	26,100	450	65,250	130	0.28

## Part Numbering - Standard Assemblies

1800 bar hose	1 metre	3 metres	6 metres	10 metres
1/4" AE tube nipple	2440D/03-04YAC-1M	2440D/03-04YAC-3M	2440D/03-04YAC-6M	2440D/03-04YAC-10M
3/8" AE tube nipple	2440D/03-06YAC-1M	2440D/03-06YAC-3M	2440D/03-06YAC-6M	2440D/03-06YAC-10M
9/16" AE tube nipple	2440D/03-09YAC-1M	2440D/03-09YAC-3M	2440D/03-09YAC-6M	2440D/03-09YAC-10M

WHAT YOU NEED.  
WHEN YOU NEED IT.



15 Magnet Road,  
Canning Vale WA 6155 | Australia  
+61 8 9456 1300 phone  
[www.tridentaustralia.com.au](http://www.tridentaustralia.com.au)