



Components

Single/Double Ferrule
Instrument Compression
Fittings

Cap

For metric tube

For capping open ended tubing



| CPI™ PART NO. | A-LOK® PART NO. | INTER- CHANGES WITH | MILLIMETERS | | | |
|------------------|--------------------|---------------------------|--------------|------|------|----------|
| | | | TUBE O.D. | A | C | W HEX |
| PNBZ 2 | BLENM2 | 2MO-C | 2 | 20,1 | 15,3 | 12,0 |
| PNBZ 3 | BLENM3 | 3MO-C | 3 | 19,8 | 15,0 | 12,0 |
| PNBZ 4 | BLENM4 | 4MO-C | 4 | 20,6 | 15,8 | 12,0 |
| PNBZ 6 | BLENM6 | 6MO-C | 6 | 23,4 | 17,8 | 14,0 |
| PNBZ 8 | BLENM8 | 8MO-C | 8 | 24,6 | 18,6 | 15,0 |
| PNBZ 10 | BLENM10 | 10MO-C | 10 | 26,7 | 19,5 | 18,0 |
| PNBZ 12 | BLENM12 | 12MO-C | 12 | 29,2 | 22,1 | 22,0 |
| PNBZ 14 | BLENM14 | 14MO-C | 14 | 29,9 | 22,0 | 24,0 |
| PNBZ 15 | BLENM15 | 15MO-C | 15 | 29,9 | 22,0 | 24,0 |
| PNBZ 16 | BLENM16 | 16MO-C | 16 | 29,9 | 22,0 | 24,0 |
| PNBZ 18 | BLENM18 | 18MO-C | 18 | 31,4 | 22,0 | 27,0 |
| PNBZ 20 | BLENM20 | 20MO-C | 20 | 34,0 | 22,0 | 30,0 |
| PNBZ 22 | BLENM22 | 22MO-C | 22 | 34,0 | 22,0 | 30,0 |
| PNBZ 25 | BLENM25 | 25MO-C | 25 | 38,4 | 26,5 | 35,0 |


NOTE: For body only specify PNZ.

Dimensions for reference only, subject to change.

A and C dimensions are typical finger-tight.

Vent Protector NPT Male Pipe Thread

For fractional tube



| CPI™ PART NO. | INTER- CHANGES WITH | THREAD SIZE | INCHES | | | |
|------------------|---------------------------|----------------|--------|-----|-------------------------|----------|
| | | | A | R | E MINIMUM OPENING | W HEX |
| 2 MDF | MS-MD-2M | 1/8-27 | 0.63 | .38 | .19 | 9/16 |
| 4 MDF | MS-MD-4M | 1/4-18 | 0.81 | .56 | .28 | 9/16 |
| 6 MDF | MS-MD-6M | 3/8-18 | 0.81 | .56 | .41 | 11/16 |
| 8 MDF | MS-MD-8M | 1/2-14 | 1.06 | .75 | .50 | 7/8 |
| 12 MDF | MS-MD-12M | 3/4-14 | 1.13 | .75 | .63 | 1-1/16 |
| 16 MDF | MS-MD-16M | 1-11-1/2 | 1.31 | .95 | .94 | 1-3/8 |

Dimensions for reference only, subject to change.

Parker Instrumentation vent protectors (mud dauber fittings) protect open ends of instruments, tubing, outlet vents, etc.

The mesh wire screen prevents foreign bodies such as insects or debris from entering and clogging various systems and causing damage.

- pipe plug, bored-thru design
- 40 x 40 mesh, .010 diameter wire screen
- designed to vent female pipe, straights, elbows or tees.

Color Coding

For easy reference, table column headings are color indicated as follows:

fractional



metric

