•

Pressure / Process Calibration Equipment

- Generate to 15,000 psi (1,000 bar) pressure
- Portable only 8.6 lbs (3.9 kg)
- Increase and decrease pressure smoothly
- Hand-tight quick connectors

Addite Metrology Made Simple



OVERVIEW

The Additel 928 Hydraulic Pressure Test Pump is a hand operated pressure pump designed to generate pressure to 15,000 psi (1,000 bar). This pump incorporates a dual-piston system which is ideal for filling large volume workload with the hand pump and providing smooth increase and decrease of pressure with the fine adjustment. The 928 Test Pump incorporates an isolation valve which isolates the calibration volume from the check valve associated with the hand pump. Because the check valve can often be a source of leaks and maintenance, the isolation valve provides more stable measurements and reduces potential maintenance of the pump. Two hand-tight quick connectors installed on the pump allow easy connecting and disconnecting to the test pump without the need for PTFE tape or wrenches. The Additel 928 is an ideal comparison test pump for calibrating pressure measuring instruments such as test gauges, indicators or transducers in the field or laboratory.

FEATURES

- Hand pump to fill large volume systems
- Portable at 8.6 lbs (3.9 kg)
- Durable and minimal maintenance Isolation valve provides stable pressures while reducing maintenance on the hand pump check valve
- Easy to use 15,000 psi (1,000 bar) can be generated easily with the dual-piston system
- Hand-tight quick connectors Allows easy connection and disconnection to the test pump without the need for PTFE tape

ORDERING INFORMATION


Mineral oil,1 bottle (250 ml)*

Carrying case (928-X-SET models only) * When water media is not requested

O-ring: 20 pcs Manual: 1 pc

Model Number

or wrenches



SPECIFICATIONS

- Media: Mineral oil or deionized water. (Oil is default media liquid. Pump with water as media to be ordered as 928W. Pump stability is best when used with oil. Performance may decrease when used with water as the media.)
- **Generated Pressure Range** 0 to 15,000 psi (1,000 bar) gauge pressure

Ram/adapters: 304 SS Body: 304 SS, aluminum Seals: Buna-N, PTFE, Copper Alloy Reservoir: UPVC

Connection

Hand-tight connectors for both test gauge and reference gauge. 1/4NPT female, 1/2NPT female, 1/4BSP female, 1/2BSP female, or M20X1.5 female

Dimensions: Height: 6.38" (162 mm) Base: 13.58" (345 mm) x 8.46" (215 mm)

Weight: 8.6 lb (3.9 kg)

Piston Volume: Fine adjust piston: 0.9 ml (0.05 in³)

Volume Per Stroke: 3.72 ml

Reservoir Volume: 150 ml (9.15 in³)

Warranty: 1 year

■ Ontional Accessories

Optional Accessories	
Description	
Oil, Diethylhexyl Sebacate, 1 liter (1 quart)	
Oil, Mineral oil, 1 liter (1 quart)	
Adapters and fittings, 1/4NPT male to various male and female connection (25 pcs). More information shown on page 70.	
Adapters and fittings, 1/4NPT (1/2NPT, 1/4BSP, 1/2BSP, or M20X1.5) male to various female hand-tight quick connectors (10 pcs). More information shown on page 71.	
Hose test kit, 5 feet flexible hose, 15,000 psi, 1/4NPT male to 1/4NPT (1/8NPT, 1/2NPT, 1/4BSP, 1/2BSP, or M20X1.5) female hand-tight quick connector.	
Carrying Case for one 928 pump and two pressure test gauges	
Maintenance kit for Additel 928 pump	
Hose Kit, External Reservoir Expansion Hose Kit for ADT928	

Phone: 714-998-6899 Fax: 714-998-6999 Email: sales@additel.com Rev # 20200629

Corporate Headquarters 2900 Saturn St #B Brea, CA 92821. USA

Salt Lake City Office 1364 West State Rd. Suite 101 Pleasant Grove, UT 84062, USA