




# HIGH VOLUME Pneumatic Diaphragm Pump

HV100SY - 4" / 100mm Slurry Valve



Yellow Series General Purpose Nylon Body – Hytrel Elastomers ATEX M2 Rating

Other materials are available to suit your specific application

Features	Benefits
> Patented design components	> Increased productivity
> Simple design with fewer wear parts	> Reduced costs – pays for itself
> Large particle handling	> Increased reliability & longer life
> Low air consumption	> Less downtime & maintenance
> Lightweight	> Easier to diagnose & repair
> Rugged & impact resistant	> Save on energy costs –
> Lubrication free	more air available for other equipment
> No end of life – can always be repaired	> Fewer injuries
> ATEX M2 certified	> No pollutants (oil free)
> Low noise levels	> Safe for hazardous environments



## Proudly Distributed By

### Pumps 2000 Pneumatic Diaphragm Pump

#### HV100SY - 4" / 100mm Slurry Valve



#### **Slurry Valve**

"Pumps 2000" pneumatic diaphragm pumps are specifically designed for harsh mining duties to outperform and outlast the competition due to a number of patented design features. The light weight feature provides ease of mobility and reduces the risk of injury. Low air consumption and long lasting lubrication free parts means low cost running and reduced maintenance. Suitable for pumping applications in all industries.

#### PRESSURE (M) HEAD (ft.) BAR PSI 70 AIR PRESSURE 100 90 AIR CONSUMPTION (SCFM) 80 50 70 60 40 50 30 20 30 20 10 10 250 US GPM FLOW Liters/min 946 1136 1325 1514 1703 1893 2081

**Performance Curve** 

	AIR PRESSURE:	Tested at 100 psi / 690 kPa (not to exceed 125 psi / 861 kPa)
	FLOW RATE:	0-540 gpm / 2044 Lpm
	FLUID CONNECTION:	4" / 100mm (Internal Thread)
	AIR INLET PORT:	1"/ 25mm (Internal Thread)
	EXHAUST PORT:	1 1/2" / 40mm (Internal Thread)
	DELIVERY PRESSURE:	Tested to 87 psi / 600 kPa
	SUCTION LIFT:	Tested to 24' / 7m dry and 30.5' / 9m wet
	SOLIDS HANDLING:	3"/75mm
	PUMP WEIGHT:	From 320 lbs / 145kg

Pumps 2000 (International)

6-12 Burleigh Street Toronto 2283 N.S.W., Australia Tel: +61 2 49599400 Fax: +61 2 49504927 info@pumps2000.com

#### Pumps 2000 (America) 1721 Main Street Pittsburgh, PA 15215 Tel: 412.963.9200 1.800.245.6211 Fax: 412.963.9214 info@pumps2000america.com

Pumps 2000 (Europe) Sunderland Tyne & Wear, SR1 2NO United Kingdom Tel: +44 (0) 191 5675488 Fax: +44 (0) 191 5678512 info@pumps2000europe.com



www.pumps2000.com

www.pumps2000america.com | www.pumps2000europe.com

Ph: +61 8 9456 1300

Web: www.tridentaustralia.com.au

Email: sales@tridentaustralia.com.au