2101 Serie S

hydrostatic Pressure test Container

















DAILY RENTAL \$1,000*

- Data is displayed clearly to operator through chart, bargraph and digital indicator displays
- Process data is logged securely to the removable memory card
- Ethernet communications provide convenient remote monitoring of the process and access to logged data
- Up to 7 analog inputs
- · Secure data recording
- Remote access and data retrieval
- Digital recording of pressure test results
- Graphical results from tests
- Emergency stop vents pressure and stops pumps from operating
- Temperature controlled
- Pressure test data plate
- Supplied with laptop and cameras on request

Trident Australia temperature controlled test bay. 3rd party engineered to withstand 30,000 psi pressure tests whilst being remotely controlled to keep the operator clear of testing hazards. Certified for offshore use this unit comes as one complete pressure testing package. **FEATURES** • DNV rated container • Twin Haskel peneumatic pumps, high volume low pressure

- and low volume high pressure
- Control panel easily disconnected to store inside test container during shipping
- 4 sling lifting bridal
- Pneumatically controlled test isolation and vent valves

SERVICES	HYDROSTATIC TEST PRESSURE
10 mm BALL	at 30,000 psi (206.85 Mpa)
1 In PIPE END	at 30,000 psi (206.85 Mpa)
2 In PIPE END	at 25,000 psi (172.38 Mpa)
3 In PIPE END	at 15,000 psi (103.43 Mpa)
4 In PIPE END	at 10,000 psi (68.95 Mpa)
INTERNAL DIMENSIONS:	2770 x 2200 x 2350 (L x W x H)









15 Magnet Road, Canning Vale WA 6155 | Australia +61 8 9456 130

www.tridentaustralia.com.au