

R2329



TRIDENT AUSTRALIA
FLUID SYSTEMS & COMPONENTS



Umbilical Reeler

Trident Australia's offshore reelers are designed with a great appreciation for the small deck space you have available on most rigs or vessels.

Another key driver for us when designing our reelers is operator and equipment safety.

Overall Frame Dimensions

Dimensions: 3,054 x 2,200 x 2,153 mm
Tare Weight: 5,500 kg
Max. Gross Weight: 8,000 kg
Certification: Designed and tested to DNV 2.7-3 R45
Compatible with R1574 and R2250

Specifications

Air Consumption: 425 cfm at 6 bar
Max Line Pull: 500 kg
Drum Speed: 5.6 rpm
Max Line Speed: 43 m/min
Clutch: Adjustable to suit umbilical SWL
Brake: Air-to-release, parking brake
Emergency Brake: Manually operated, air over hydraulic
Spooling Gear: Automatic spooling level wind
Controls: Isolation valve and gauge on each line
Core Diameter: 1,200 mm
Flange Diameter: 1,700 mm
Drum Width: 1,100 mm

All of Trident Australia's rental equipment is checked and serviced before every rental job to ensure you get the best product and experience every time

WHAT YOU NEED.
WHEN YOU NEED IT.



15 Magnet Road,
Canning Vale WA 6155 | Australia
+61 8 9456 1300 phone
www.tridentaustralia.com.au