

# R1644



**TRIDENT AUSTRALIA**  
FLUID SYSTEMS & COMPONENTS



## Umbilical Reeler

Trident Australia's offshore reelers are designed with a great appreciation for the small deck space you have available on most rigs or vessels. Another key driver for us when designing our reelers is operator and equipment safety.

## Specifications

Air Consumption:	382 cfm at 6 bar
Max Line Pull:	1,500 kg
Drum Speed:	6.8 rpm
Max Line Speed:	40 m/min
Park Brake:	Factory set parking brake
Emergency Brake:	Manually operated locking pin
Spooling Gear:	Automatic spooling level wind
Controls:	Isolation valve and gauge on each line
Core Diameter:	1,416 mm
Flange Diameter:	2,200 mm
Drum Width:	1,350 mm

## Overall Frame Dimensions

Dimensions:	2,945 x 2,380 x 2,702 mm
Tare Weight:	5,300 kg
Gross Weight:	6,855 kg
Certification:	Designed and tested to DNV 2.7-3 R30
Drawing No:	02012-0101
CCLE:	058 CCLE 001

System designed to suit R1266; Compatible with R1574

*All of Trident Australia's rental equipment is checked and serviced before every rental job to ensure you get the best product and experience every time*

WHAT YOU NEED.  
WHEN YOU NEED IT.



15 Magnet Road,  
Canning Vale WA 6155 | Australia  
+61 8 9456 1300 phone  
[www.tridentaustralia.com.au](http://www.tridentaustralia.com.au)