

# R1649



**TRIDENT AUSTRALIA**  
FLUID SYSTEMS & COMPONENTS



## Umbilical Reeler

Trident Australia's offshore reelers are designed with a great appreciation for the small deck space you have available on most rigs or vessels. Another key driver for us when designing our reelers is operator and equipment safety.

## Specifications

Air Consumption:	297 cfm at 5 bar
Max Line Pull:	2,100 kg
Drum Speed:	5.8 rpm
Max Line Speed:	42 m/min
Park Brake:	Factory set parking brake
Emergency Brake:	Manually operated locking pin
Spooling Gear:	Automatic spooling level wind
Controls:	Isolation valve and gauge on each line
Core Diameter:	1,000 mm
Flange Diameter:	2,600 mm
Drum Width:	1,460 mm

## Overall Frame Dimensions

Dimensions:	2,353 x 4,003 x 3,116 mm
Tare Weight:	5,730 kg
Gross Weight:	10,000 kg
Certification:	Designed and tested to DNV 2.7-3 R45
Drawing No:	04313-0101
CCLE:	072 CCLE 001

System designed to suit R1454 and R1650

*All of Trident Australia's rental equipment is checked and serviced before every rental job to ensure you get the best product and experience every time*

WHAT YOU NEED.  
WHEN YOU NEED IT.



15 Magnet Road,  
Canning Vale WA 6155 | Australia  
+61 8 9456 1300 phone  
[www.tridentaustralia.com.au](http://www.tridentaustralia.com.au)